



The palm grip B 5 is an actuating element for our multi-axis and single-axis controller. It can also be used as an actuating element for hydraulic drives. Push buttons, rocker switches, e.t.c., can also be fitted to suit appropriate requirements.

The palm grip has a highly flexible cable 4 (8) x 0,25 mm² x 450 mm long.

The mounting piece for the drive rod can be supplied with a tapped hole M 8 or M 10 (standard = M 10).

The palm grip B 5 is made of PA plastic and is black in colour.

Contact complement 2 A 250 V AC 15 / 3 A 24 V DC 13
or 0,5 A 250 V AC 15 / 1,5 A 24 V DC 13

Permissible ambient temperature Operating -40°C to +60°C
Storage -50°C to +80°C

Climate resistance
Damp heat constant
Damp heat cyclic
Degree of protection front

DIN IEC 68 part 2-3
DIN IEC 68 part 2-30
IP 54 IEC 529 DIN 40050

Pos.				Contact-complement	Weight gramm	Type	Price EURO
1		without built in		KBAD / 254		B 5	
2 3 4		Rocker switch top tast-0-tast Rocker switch top tast-0-rest Rocker switch top rest-0-rest	T-0-T installed Pos. 1 T-0-R installed Pos. 1 R-0-R installed Pos. 1	KBAD / 248	2 change over contact 2 A 250 V AC 15	B 5 W	
5		Rocker switch top tast-0-tast with push button side	T-0-T installed Pos. 1 installed Pos. 2	KBAD / 294	2 change over contact 2 A 250 V AC 15 1 change over contact 0,5A 250 V AC 15	B 5 WD	
7 8		Push button top mechanical operation Push button top	installed Pos. 1 installed Pos. 1	KBAD / 311 KBAD / 250	1 change over contact 0,5 A 250 V AC 15	B 5 T B 5 D	
9		Push button top with 1 push button side	installed Pos. 1 installed Pos. 2	KBAD / 252	2 change over contact 0,5 A 250 V AC 15	B 5 2D	
11 12		1 push button side 2 push button side	installed Pos. 1 installed Pos. 2	KBAD / 246	change over contact 0,5 A 250 V AC 15	B 5 D B 5 2D	
21 22		Cable 4 res. 8 x 0,25 mm ² x 450 mm long wired included in Pos. 1-12 Additional price per metre cable 4-pole Additional price per metre cable 8-pole					