



The palm grip B 6 is an actuating element for our multi-axis and single-axis controller. It can also be used as an actuating element with hydraulic drives. Push buttons, rocker switches, e.t.c., can also be fitted to suit appropriate requirements. These devices have micro changeover contacts.

The palm grip has a highly flexible cable 4 (8) x 0,25 mm² x 450 mm long.

The mounting piece for the drive rod can be supplied with a tapped hole M 8 or M 10 (standard = M 10).

The palm grip B 6 is made of PA plastic and is black in colour.

Contact complement 2 A 250 V AC 15 / 3 A 24 V DC 13
or 0,5 A 250 V AC 15 / 1,5 A 24 V DC 13

Permissible ambient temperature Operating -40°C to +60°C
Storage -50°C to +80°C

Climate resistance
Damp heat constant DIN IEC 68 part 2-3
Damp heat cyclic DIN IEC 68 part 2-30
Degree of protection front IP 54 IEC 529 DIN 40050

Pos.			Contact-complement	Weight gramm	Type	Price EURO
1		with built in lever switch side 0-tast	1 change over contact 0,5 A 250 V AC 15	120	B 6 K	
2		Lever switch side 0-tast	3 change over contact 0,5 A 250 V AC 15	130	B 6 KW	
3	with rocker switch top tast-0-tast T-0-T					
4	with rocker switch top tast-0-rest T-0-R with rocker switch top rest-0-rest R-0-R					
5		Lever switch side 0-tast with push button top	2 change over contact 0,5 A 250 V AC 15	130	B 6 KD	
21		Cable 4 res. 8 x 0,25 mm ² x 450 mm long wired included Pos. 1-5				
22		Additional price per metre cable 4-pole Additional price per metre cable 8-pole				