



Manufacture Siemens 3 SB 22 mm

Pos.	Command devices			Weight gramm	Type	Price EURO
1	Push button		1 NO + 1 NC	40	D	
2	Selector switch 0-1	2 positions	1 NO + 1 NC	50	W	
3	Selector switch 1-0-2	3 positions	2 NO + 2 NC	60	W	
4						
5						
6	Key switch 0-1	2 positions	1 NO + 1 NC	130	S	
7	Key switch 1-0-2	3 positions	2 NO + 2 NC	140	S	
8						
9						
10	Mushroom key switch latching		1 NO + 1 NC	80	PS	
11	Mushroom head push button latching		1 NC	60	PV	
12						
13						
14						
15	Contact block additional (max. 3 pcs.)		1 NO + 1 NC	10		
	Command and indicating devices					
16	Illuminated push button lamp 24 V AC		1 NO + 1 NC	40	LD	
17	Illuminated push button lamp 110 V operating voltage 220 V AC		1 NO + 1 NC	40	LD	
18	Illuminated push button lamp 24 V with transformer 220/24 V AC		1 NO + 1 NC	50	LD	
19						
20	Contact block additional (max. 3 pcs.)		1 NO + 1 NC	10		
	Indicating devices					
21	Indicator light lamp 24 V AC			40	L	
22	Indicator light lamp 110 V operating voltage 220 V AC			40	L	
23	Indicator light lamp 24 V with transformer 220/24 V AC			50	L	
24						
25						
	Special devices					
26	Drilling diameter 22 mm					
27	Blind plug 22					
28						
29	Push button with 2 steps SES 2		2 NO + 1 NC	300		
30	Push button with 2 steps ST 1-3-2		2 NO + 1 NC	300		
31	Push button with 3 steps ST 1-4-3		3 NO + 1 NC	350		
32	Push button with 4 steps ST 1-5-4		4 NO + 1 NC	400		
33	Push button with potentiometer PT 1-2-P		1 NO + 1 NC	350		
34	Wire-wound potentiometer T 237 linear Life 10 ⁸ switching cycles					
35	resistance 0,5/1,0/2,0/5,0 kOhm 1 Watt wiper current max. 10 mA					
36	Drive for potentiometer M4168 with friction brake, switching sequence -0-, contact (potentiometer look 1/240)			250		
37	Summer EKS 24 V DC / 48 V AC / 220 V AC			250		
38	Knee button FAK-S/KC/I		1 NO + 1 NC	350		
39	Foot button 3SE 3902-OAB20		1 NO + 1 NC	450		
40						