



Type KST3KFS2-...

The crane control unit KST 3 combines in its design the crane driver's seat and the control and monitoring devices. Ready wired, it can be easily and quickly installed in the crane cabin.

Equipment boxes: Plastic polyester.

The equipment boxes with the devices fitted have hinged tops that can be locked in position and armrests. They contain the termination and connection facilities and a lockable plug-in cover on the inside.

Seat KFS 2: The seat backrest can be tipped forwards and further tipped together with the cushion.

The cushion and seat backrest are padded.

Adjusting possibilities: Cushion horizontally and vertically.

Height adjustment via a gas-loaded spring in the seat base.

Seat backrest horizontally and vertically to the cushion.

Armrests padded and adjustable in height.

Fixed to the equipment boxes.

Surface treatment: Anti-corrosion primer, top coat: 2 coats of epoxy-resin paint, standard colour RAL 7032 pebble-grey, textured Varnish

All non-painted metal parts are electrogalvanized and chromed.

Description data see catalog 5/003/004

Permissible ambient temperature	Operation -40° C to +60° C
	Storage -50° C to +80° C
Climate resistance	
Damp heat constant	DIN IEC 68 part 2-3
Damp heat cyclic	DIN IEC 68 part 2-30
Degree of protection	IP 54 IEC 529 DIN 40050

Pos.					Weight kg	Type	Price EURO
1	Crane control unit with driver's seat	KFS 2	with base plate		36	KST 3	
2	Crane control unit with driver's seat	KFS 2	without base plate		31	KST 31	
3	Crane control unit without driver's seat	KFS 2	with base plate		21	KST 32	
4	Crane control unit without driver's seat	KFS 2	without base plate		16	KST 33	
5							
10	Driver's seat	see catalog 2/130 (picture shows)				KFS 2	
11							
12	Driver's seat	see catalog 2/132				KFS 4	
13							
14							
15	Driver's seat	see catalog 2/140				KFS 9	
20	Multi-axis controller	see catalog 1/100					
21	Single-axis controller	see catalog 1/200					
22							
23	Control-switch	see catalog 1/220					
24	Command and indicating devices	see catalog 1/360					
25							
30	Terminal block 4 mm ² without wiring each terminal					KL	
31	Terminal block 4 mm ² with wiring wire 1,5 mm ² each terminal					KL	
32	External wiring single wire highly flexible 1,5 mm ² 5 metre long						
33	Additional or subtract price each metre						
34							
35							
40	Special painted						
41	Indicating labels not engraved with 2 or 4 arrows						
42	Engraving, each 10 characters						
43							

