



Type KST75KFS2-...

The crane control unit KST 75 combines in its design the crane driver's seat and the control and monitoring devices. Ready wired, it can be easily and quickly installed in the crane cabin.

Equipment boxes: Sheet steel.

The equipment boxes with the devices fitted have hinged tops that can be locked in position and armrests. They contain the termination and connection facilities and a lockable plug-in cover on the inside.

Seat KFS 2: The seat backrest can be tipped forwards and further tipped together with the cushion. The cushion and seat backrest are padded.

Adjusting possibilities: Cushion horizontally and vertically. Height adjustment via a gas-loaded spring in the seat base. Seat backrest horizontally and vertically to the cushion. Armrests padded and adjustable in height. Fixed to the equipment boxes.

Surface treatment: Anti-corrosion primer, top coat: 2 coats of epoxy-resin paint, standard colour RAL 7032 pebble-grey. textured varnish
All non-painted metal parts are electrogalvanized and chromed.

Description data see catalog 5/003/004

Permissible ambient temperature	Operation -40° C to +60° C Storage -50° C to +80° C
Climate resistance	
Damp heat constant	DIN IEC 68 part 2-3
Damp heat cyclic	DIN IEC 68 part 2-30
Degree of protection	IP 54 IEC 529 DIN 40050

Pos.					Weight kg	Type	Price EURO
1	Crane control unit with driver's seat	KFS 2	with base plate		51	KST 75	
2	Crane control unit with driver's seat	KFS 2	without base plate		46	KST 76	
3	Crane control unit without driver's seat	KFS 2	with base plate		36	KST 77	
4	Crane control unit without driver's seat	KFS 2	without base plate		31	KST 78	
5							
10	Driver's seat	see catalog 2/130 (picture shows)				KFS 2	
11							
12	Driver's seat	see catalog 2/132				KFS 4	
13							
14							
15	Driver's seat	see catalog 2/140				KFS 9	
20	Multi-axis controller	see catalog 1/100					
21	Single-axis controller	see catalog 1/200					
22	Double-handle	see catalog 1/160					
23	Control-switch	see catalog 1/220					
24	Command and indicating devices	see catalog 1/360					
25							
30	Terminal block 4 mm ² without wiring each terminal					KL	
31	Terminal block 4 mm ² with wiring wire 1,5 mm ² each terminal					KL	
32	External wiring single wire highly flexible 1,5 mm ² x 5 metre long						
33	Additional or subtract price each metre						
34							
35							
40	Special painted						
41	Indicating labels not engraved with 2 or 4 arrows						
42	Engraving, each 10 characters						
43							

