



U22/32 / N61.../N62... / H / PW / 2D / PQ / KLV / X

Command and indicating devices							
H	Heating	20 Watt 220 or 110V 50/60 Hz					
PV	Mushroom head push button latching	22 latching with indicating label	1 NC				
P	Mushroom head push button	22 with indicating label	1 NO				
D	Push button	22 with indicating label	1 NO				
W	Selector switch 0-1	22 with indicating label	1 NO				
L	Indicator light	22 with indicating label	Diode 24 Volt				
L	Indicator light	22 with indicating label	Diode 230 Volt AC				
	Contact block additional		1 S or 1 Ö				
L	Indicator light	22 with indicating label	Diode 24 Volt protection IP65				
L	Indicator light	10 with indicating label	Diode 24 Volt protection IP65				
Display devices							
PQ	Powermeter PQ 72 1 mA DC		Engraved your instructions				
PQI	Powermeter PQ 72 1 mA DC illuminated 24 Volt		Engraved your instructions				
PQ	Powermeter PQ 72 x 36 1 mA DC		Engraved your instructions				
PQI	Powermeter PQ 72 x 36 1 mA DC illuminated 24 Volt		Engraved your instructions				
EQ	Amperemeter EQ 72 100/200/1A		Engraved your instructions				
EQI	Amperemeter EQ 72 100/200/1A illuminated 24 Volt		Engraved your instructions				
EQ	Amperemeter EQ 72 x 36 100/200/1A		Engraved your instructions				
EQI	Amperemeter EQ 72 x 36 100/200/1A illuminated 24 Volt		Engraved your instructions				
Wiring		KLV on terminal block 2,5mm <sup>2</sup> with wire line 0,75 mm <sup>2</sup>					
Special model		X Special / customer specified					

