

Double-Handle Controller

D85



GESSMANN®

The Double-Handle Controller D85 is a robust switching device for electro hydraulic and hoisting applications. Long life and high reliability is ensured by the latest contactless hall-technology. The modular design enables the switching device to be used universally.

Technical data

Mechanical life D85	8 million operating cycles
Operation temperature	-40°C to +85°C
Degree of protection	IP54 front



		Example										
		D85	S5	Q	/	Q	-Z	+R	-B	-E...	-S...	-X
Basic unit												
D85	Double-Handle Controller											
Control-handle extended												
	Standard 160 mm*											
S5	-20 mm											
S8	+20 mm											
*Only available in combination with handle!												
Grip- control-handle left												
	Knob											
M	Mechanical zero interlock											
T	Dead man											
H	Signal button											
D	Push button											
Q	T-grip											
QD	T-grip with push button side											
B10...	Palm Grip B10... (see page 196)											
Grip- control-handle right												
See grip-control-handle left												
Axis 1: direction 1-2 left												
Z	Spring return											
R	Friction brake											
Axis 2: direction 3-4 left												
Z	Spring return											
R	Friction brake											

Technical details may vary based on configuration or application! Technical data subject to change without notice!

	D85	S5	Q / Q	-Z	+R	-B	-E...	-S...	-X
Cover housing									
B	Cover housing								
Interface (description see following pages)									
E1xx	Voltage output								
E2xx	Current output								
E3xx	CAN-interface								
E4xx	CAN Safety								
E5xx	Profibus DP interface								
E6xx	Profinet								
E7xx	PROFIsafe								
E8xx	PWM output								
E9xx	Other outputs								
Plug connectors									
S...	Standard plug connectors (see page 127)								
Special model									
X	Special/ customer specified								

Combination possibilities with our handles



Digital output				
Supply voltage	9-32 V DC			
Current carrying capacity	Direction signal 150 mA			
	Zero position signal 500 mA			
Mounting depth A	85 mm			
Wiring	Cable 500mm long without plug connector			
	Optional with plug connector (standard plug connectors see page 127)			S
2 direction signals + 1 zero position signal (Galvanically isolated) per axis				
	2 axis		E001 2	

Voltage output (not stabilized)				
Supply voltage	4,75-5,25 V DC			
Current carrying capacity	Direction signal 8 mA			
Mounting depth A	85 mm			
Wiring	Cable 500 mm long without plug connector			
	Optional with plug connector (standard plug connectors see page 127)			S
0,5...2,5...4,5V redundant + 2 direction signals per axis				
	2 axis		E104 2	
	Output options			
	Characteristic:			
	Inverse dual			1
	Dual			2
	Inverse dual with dead zone +/- 3° (standard)			3
	Dual with dead zone +/- 3°			4

Voltage output			
Supply voltage	9-32 V DC (*11,5-32)		
Current carrying capacity	Direction signal 150 mA		
	Zero position signal 500 mA		
Mounting depth A	85 mm		
Option	Input for capacitive sensor		
Wiring	Cable 500 mm long without plug connector		
	Optional with plug connector (<i>standard plug connectors see page 127</i>)		S
0,5...2,5...4,5 V redundant + 2 direction signals + 1 zero position signal (galvanically isolated) per axis			
	2 axis	E112 2	
0...5...10 V redundant + 2 direction signals + 1 zero position signal (galvanically isolated) per axis, supply voltage 11,5 - 32 V DC			
	2 axis	E132 2	
10...0...10 V + 2 direction signals + 1 zero position signal (galvanically isolated) per axis, supply voltage 11,5 - 32 V DC, sensor redundant with error monitoring and error signal			
	2 axis	E136 2	
+10...0...-10 V + 2 direction signals + 1 zero position signal (galvanically isolated) per axis, supply voltage 11,5 - 32 V DC, sensor redundant with error monitoring			
	2 axis	E138 2	
Output options			
Characteristic:			
Inverse dual *1			1
Dual *1			2
Inverse dual with dead zone +/- 3° *1 (standard)			3
Dual with dead zone +/- 3°*1			4
*1 Not combinable with output E136X and E138X			
Single *2			5
Single with dead zone +/- 3° *2 (standard)			6
*2 Not combinable with output E112X and E132X			
Digital output signals:			
Output signals standard:			
Direction signals and zero position signals 1,5A 24 V DC			1
Voltage output with other value on request!			

Current output

Supply voltage	9-32 V DC		
Current carrying capacity	Direction signal 150 mA Zero position signal 500 mA		
Mounting depth A	85 mm		
Option	Input for capacitive sensor		
Wiring	Cable 500 mm long without plug connector		
	Optional with plug connector (<i>standard plug connectors see page 127</i>)		S
0...10...20 mA + 2 direction signals + 1 zero position signal (galvanically isolated) per axis, sensor redundant with error monitoring and error signal	2 axis	E206 2	
20...0...20 mA + 2 direction signals + 1 zero position signal (galvanically isolated) per axis, sensor redundant with error monitoring and error signal	2 axis	E208 2	
4...12...20 mA + 2 direction signals + 1 zero position signal (galvanically isolated) per axis, sensor redundant with error monitoring and error signal	2 axis	E214 2	
20...4...20 mA + 2 direction signals + 1 zero position signal (galvanically isolated) per axis, sensor redundant with error monitoring and error signal	2 axis	E216 2	
+20...0...-20 mA + 2 direction signals + 1 zero position signal (galvanically isolated) per axis, sensor redundant with error monitoring and error signal	2 axis	E226 2	
Output options			
	Single		5
	Single with dead zone +/- 3° (standard)		6
Digital output signals:			
Output signals standard:			
	Direction signals and zero position signals 1,5A 24 V DC		1

Current output with other value on request!

CAN

Supply voltage	9-36 V DC
Idle current consumption	120 mA
Current carrying capacity	Direction signal 100 mA Zero position signal 100 mA External digital output for LEDs 5-30 mA (dependent on the number of LEDs) Digital switching output (potential-free) 100 mA
Mounting depth A	E3181: 85 mm E3181X: 105 mm E3191X - E3193X: 105 mm E3194X - E3195X: 125 mm
Protocol	CANOpen CiA DS 301 or SAE J 1939 (Based on)
Baud rate	125 kBit/s to 1 Mbit/s (standard 250 kBit/s)
Output value	255...0...255
Wiring	CAN (IN) cable 300 mm with plug connector M12 (male) CAN (OUT) cable 300 mm with plug connector M12 (female) External in-/outputs cable 300 mm without plug connector External in-/outputs cable 300 mm without plug connector (additionally from 32 in-/outputs)

Technical details may vary based on configuration or application! Technical data subject to change without notice!

Optional with plug connector (standard plug connectors see page 127)		S
CAN expansion stage 1		E318 1
- 8 analog joystick axis - 16 digital joystick functions - Input for capacitive sensor - Output for vibrator control		
With additional external in-/outputs		
- 8 external LED-outputs (dimmable optional), 1 switching output (potential-free, 100 mA), 8 external digital inputs		2
- 16 external LED-outputs (dimmable optional), 1 switching output (potential-free, 100 mA), 16* external digital inputs		3
*External LED-outputs can be used for LEDs in the grip		
(Control of intelligent RGB LEDs possible on request)		
*With the use of capacitive sensor, the external digital inputs are reduced by one input!		
CAN expansion stage 2		E319 1
- 14 analog joystick axis - 16 digital joystick functions - 2 inputs for capacitive sensors - Output for vibrator control		
With additional external in-/outputs		
- 8 external LED-outputs (dimmable optional), 1 switching output (potential-free, 100 mA), 8 external digital inputs		2
- 16 external LED-outputs (dimmable optional), 1 switching output (potential-free, 100 mA), 16 external digital inputs		3
- 24 external LED-outputs (dimmable optional), 1 switching output (potential-free, 100 mA), 24 external digital inputs		4
- 32 external LED-outputs (dimmable optional), 1 switching output (potential-free, 100 mA), 32* external digital inputs		5
*External LED-outputs can be used for LEDs in the grip!		
(Control of intelligent RGB LEDs possible on request)		
Main-axis with additional digital-/analog outputs separately wired (not via CAN)		
- 2 direction signals + 1 zero position signal (potential-free) per main-axis		3
Additional analog outputs on request!		

CAN Safety	
Supply voltage	9-36 V DC
Idle current consumption	120 mA
Current carrying capacity	Direction signal 100 mA
	Zero position signal 100 mA
	External digital output for LEDs 5-30 mA (depending on the number of LEDs)
	Digital switching output (potential-free) 100 mA
Mounting depth A	E4181: 85 mm
	E4181X: 105 mm
	E4191X - E4193X: 105 mm
	E4194X - E4195X: 125 mm
Protocol	CAN Safety EN50325-5 or J1939-76
Baud rate	125 kBit/s to 1 MBit/s (standard 250 kBits)
Wiring	CAN (IN) cable 300 mm with plug connector M12 (male)
	CAN (OUT) cable 300 mm with plug connector M12 (female)
	External in-/outputs cable 300 mm without plug connector
	External in-/outputs cable 300 mm without plug connector (additionally from 32 in-/outputs)

Optional with plug connector (standard plug connectors see page 127)		S
CAN Safety expansion stage 1	E418 1	
- 8 analog joystick axis		
- 16 digital joystick functions		
- 1 Input for capacitive sensor		
- Output for vibrator control		
With additional external in-/outputs		
- 8 external LED-outputs (dimmable optional), 1 switching output (potential-free, 100 mA), 8 external digital inputs	2	
- 16 external LED-outputs (dimmable optional), 1 switching output (potential-free, 100 mA), 16* external digital inputs	3	
External LED-outputs can be used in the grip for LEDs		
(Control of intelligent RGB LEDs possible on request)		
*With the use of capacitive sensor, the external digital inputs reduce by one input!		
CAN Safety expansion stage 2	E419 1	
- 14 analog joystick axis		
- 16 digital joystick functions		
- Output for vibrator control		
With additional external in-/outputs		
- 8 external LED-outputs (dimmable optional), 1 switching output (potential-free, 100 mA), 8 external digital inputs	2	
- 16 external LED-outputs (dimmable optional), 1 switching output (potential-free, 100 mA), 16* external digital inputs	3	
- 24 external LED-outputs (dimmable optional), 1 switching output (potential-free, 100 mA), 24 external digital inputs	4	
- 32 external LED-outputs (dimmable optional), 1 switching output (potential-free, 100 mA), 32* external digital inputs	5	
External LED-outputs can be used in the grip for LEDs		
(Control of intelligent RGB LEDs possible on request)		
Main-axis with additional digital-/analog outputs separately wired (not via CAN)		
- 2 direction signals + 1 zero position signal (potential-free) per main-axis		3
Additional analog outputs on request!		

Profibus DP		
Supply voltage	18-30 V DC	
Baud rate	To 12 MBit/s	
Output value	0...128...255	
Mounting depth A	105 mm	
Wiring	Profibus, cable 100 mm with plug D-Sub 9	
	Supply voltage (if applicable contact wiring) cable 12 x 0,25 mm ² 300 mm long without plug connector	
	External in-/outputs, cable 300 mm long without plug connector	
Optional with plug connector (standard plug connectors see page 127)		S
Profibus DP	E501 1	
- 4 analog joystick axis		
- 16 digital joystick function		
- Input for capacitive sensor		
With additional external in-/outputs		
- 8 external LED-output, 8 external digital input	2	
- 16 external LED-output, 16 external digital input	3	
External LED-outputs can be used in the grip for LEDs		
With additional contact equipment separately wired (not via profibus)		
- 2 direction contacts + 1 zero position contact (not potential-free) per main-axis		1
- 1 zero position contact (potential-free) per main-axis		2

Profinet			
Supply voltage	18-30 V DC		
Baud rate	To 100 MBit/s		
Output value	0...512...1023		
Mounting depth A	105 mm		
Verdrahtung	Profinet (1), cable 300 mm with M12 plug connector (female)		
	Profinet (2), cable 300 mm with M12 plug connector (female)		
	Supply voltage (if applicable contact wiring) cable 12 x 0,25 mm ² 300 mm long without plug connector		
	External in-/outputs, cable 300 mm long without plug connector		
	Optional with plug connector (<i>standard plug connectors see page 127</i>)		S
Profinet		E603 1	
- 6 analog joystick axis			
- 24 digital joystick functions			
- Input for capacitive sensor			
With with additional external in-/outputs			
- 8 external LED-outputs, 8 external digital inputs		2	
- 16 external LED-outputs, 16 external digital inputs		3	
*External LED-outputs can be used for LEDs in the grip!			
Main-axis with additional signals separately wired (not via profinet)			
- 2 direction signals + zero position signal (potential-free) per main-axis			3

PROFIsafe			
Supply voltage	18-30 V DC		
Baud rate	To 12 MBit/s		
Output value	0...512...1023		
Mounting depth A	105 mm		
Wiring	Profinet (1), cable 300 mm with M12 plug connector (female)		
	Profinet (2), cable 300 mm with M12 plug connector (female)		
	Supply voltage (if applicable contact wiring) cable 12 x 0,25 mm ² 300 mm long without plug connector		
	External in-/outputs, cable 300 mm long without plug connector		
	Optional with plug connector (<i>standard plug connectors see page 127</i>)		S
PROFIsafe		E703 1	
- 6 analog joystick axis			
- 24 digital joystick functions			
- Input for capacitive sensor			
With additional external in-/outputs			
- 8 external LED-outputs, 8 external digital inputs		2	
- 16 external LED-outputs, 16 external digital inputs		3	
*External LED-outputs can be used for LEDs in the grip!			
Main-axis with additional signals separately wired (not via profinet safe)			
- 2 direction signals + zero position signal (potential-free) per main-axis			3

PWM Outputs

Supply Voltage:	9-32 V DC		
Valve control current:	Max. 3 A		
PWM-frequency:	1225 Hz		
Dither frequency:	1...250 Hz adjustable		
Mounting depth A	85 mm		
Other features	Creep speed per axis 5 configurable switching outputs 2A LED outputs for status indication Input for redundant deadman		
Wiring:	Built-in socket Phoenix 2-pole (power supply) Cable 1 (PWM) 12 x 1 mm ² 300 mm long without plug Cable 2 (switching output) 12 x 1 mm ² 300 mm long without plug Cable 3 (Creep speed / dead man) 14 x 0,25 mm ² 300mm long without plug Optional with plug connector (standard plug connectors see page 127)		
PWM Output 0-3 A for 2 proportional valve magnets per axis	2 axis	E801 2	S

Other outputs

Voltage output for PVG32 0,25...0,5...0,75 Us, power supply 9-32 V DC			
Option	Input for capacitive sensor		
Wiring	Cable 14 x 0,25 mm² 300 mm long without plug connector		
	Optional with plug connector (<i>standard plug connectors see page 127</i>)		S
	2 axis	E907 2	
Main-axis with additional direction contacts per main-axis			4
8 Bit Gray-Code with direction signals per main-axis, supply voltage 9-36 V DC			
Wiring:	Cable 37 x 0,14 mm² 300 mm long without plug connector (axis 1+2)		
	Optional with plug connector (<i>standard plug connectors see page 127</i>)		S
	2 axis	E903 2	
8 Bit Binär-Code with direction signals per main-axis, supply voltage 9-36 V DC			
Wiring:	Cable 37 x 0,14 mm² 300 mm long without plug connector (axis 1+2)		
	Optional with plug connector (<i>standard plug connectors see page 127</i>)		S
	2 axis	E904 2	

Attachments

Z01 Mating connector (CAN) M12 (male insert) with 2 m cable	20201140
Z02 Mating connector (CAN) M12 (female contact) with 2 m cable	20202298
Z03 Mating connector (Profibus) straight	22201440
Z04 Mating connector (Profibus) 90° angled	22201741
Z05 Mating connector (Profinet) M12 (male insert) with 2 m cable	5300000222



Double-Handle Controller D85

GESSMANN®




T = Dead man's button
H = Signal button

Knob solid
D= Push button

T - grip
D= Push button



To build in:
Direction 1-2
Direction 3-4



Palm grip B10

