

The Control Pedestal U22/32 accomodate the devices necessary for control and monitoring. Ready wired, it can be quickly and easily installed on the sea deck. The housing (pedestal head) is made of seawater-resistant aluminium.

Surface treatment:
Priming and structure-finishing paint
Standard colour RAL 7032 pebble-grey

Technical data:

Operation temperature	-40°C to +85°C
Degree of protection	IP66



		U22/32		/	N61.../ N62...		/	H / PW / 2D		/	PQ	/	KLV	/	X
Housing															
U22/32	With 1 narrow side-plate with pillar-gasket														
FD	Side-plate narrow gasket														
HD	Side-plate wide gasket (required for command and indicating devices)														
KD	Hinged side-plate with gasket that can be locked in position														
IA	Monitoring devices cover with gasket for max. 2 monitors 72 x 72 mm or 4 monitors 72 x 36 mm and max. 6 indicating devices pos. 28, 29														
RS	Pillar 108 mm Ø 670 mm height with flange quadratic or round														
Masterswitch / Control-Switch															
N61	HG Masterswitch with ball handle and indicating labels														
N62	KN Control-Switch with knob and indicating label														
		-HG	-01 Z P	-A05	P134	-X									
Axis 1: direction 3-4															
		(Standard contacts gold-plated 2A 250 V AC15)													
01	2 contacts	Standard contact - arrangement see page 129													
02	4 contacts	z.B.													
03	6 contacts	A05	MS21												
04	8 contacts	A0500	MS21-00												
		A99 contact - arrangement according customer request													
Z	Spring return														
R	Friction brake														
P	Potentiometer	P131	T396 2 x 0,5 kOhm	I max. 1 mA											
		P132	T396 2 x 1 kOhm	I max. 1 mA											
		P133	T396 2 x 2 kOhm	I max. 1 mA											
		P134	T396 2 x 5 kOhm	I max. 1 mA											
		P135	T396 2 x 10 kOhm	I max. 1 mA											
		More potentiometers on request!													

Technical details may vary based on configuration or application! Technical data subject to change without notice!

U22/32 / N61.../N62... / H / PW / 2D / PQ / KLV / X

Command and indicating devices

H	Heating	20 Watt 220 or 110V 50/60 Hz	
PV	Mushroom head push button latching	22 latching with indicating label	1 NC
P	Mushroom head push button	22 with indicating label	1 NO
D	Push button	22 with indicating label	1 NO
W	Selector switch 0-1	22 with indicating label	1 NO
L	Indicator light	22 with indicating label	Diode 24 Volt
L	Indicator light	22 with indicating label	Diode 230 Volt AC
	Contact block additional		1 S or 1 Ö
L	Indicator light	22 with indicating label	Diode 24 Volt protection IP65
L	Indicator light	10 with indicating label	Diode 24 Volt protection IP65

Display devices

PQ	Powermeter PQ 72 1 mA DC	Engraved your instructions
PQI	Powermeter PQ 72 1 mA DC illuminated 24 Volt	Engraved your instructions
PQ	Powermeter PQ 72 x 36 1 mA DC	Engraved your instructions
PQI	Powermeter PQ 72 x 36 1 mA DC illuminated 24 Volt	Engraved your instructions
EQ	Amperemeter EQ 72 100/200/1A	Engraved your instructions
EQI	Amperemeter EQ 72 100/200/1A illuminated 24 Volt	Engraved your instructions
EQ	Amperemeter EQ 72 x 36 100/200/1A	Engraved your instructions
EQI	Amperemeter EQ 72 x 36 100/200/1A illuminated 24 Volt	Engraved your instructions

Wiring

KLV on terminal block 2,5mm² with wire line 0,75 mm²

Special model

X Special / customer specified

